#whdentalwerk (f) (◎ (in)) video.wh.com Now at your dealer or **wh.com**

The breakthrough in **oral surgery**



WSH





Modularity

The modularity offers the possibility of adapting the device to the requirements of the individual user.



Automatic instrument detection

Piezomed detects the instrument when it is inserted and automatically sets the right power class.



Efficient cooling of the operating site

The spray is expelled close to the instrument's area of activity and thus provides ultra-efficient cooling of the operating site.



Instrument library

Enables the individual setting of the most important treatment parameters for the preferred instruments.



業

Absolute freedom of movement

The wireless foot control allows you to choose the optimal location in your working area. This ensures a level of safety in the treatment area.

Cooling without case fan

This prevents disruptive noises. No impairment of the sterile environment due to the emission of cooling air.



Modularity for optimal **flexibility**

Workflow driven solution

The combination of Implantmed Plus and Piezomed module changes the way oral surgery and implantology work.

Electric motor Particularly small and surprisingly light. It enables you to work with ease.





Straight & Contra-angle Handpieces Provide optimal illumination of the treatment site and facilitate perfect, accurate treatment results.





Osstell Beacon

Bluetooth connection to the Osstell Beacon for easy measurement of implant stability.



| | | max | .37 | |
|-----|---------|-----|-----|---|
| مہر | | | | |
| | | | | |
| | 28.42.4 | | | L |

Documentation of osseointegration

The documentation function conveniently saves all values of the implant insertion on a USB stick (.pdf and .xls).



Features at a glance





| Features | Piezomed | Piezomed Plus module | Piezomed Classic module |
|---|--|-------------------------|--|
| Automatic instrument detection | 1 | 1 | |
| Instrument library | | 1 | |
| Modularity | | 1 | 1 |
| Wireless foot control | 1 | 1 | 1 |
| Control unit cooling without case fan | Image: A second s | 1 | × |
| Osstell Beacon connection | | 1 | × |
| Implantmed and Piezomed functions can be controlled with just one foot control | × | 1 | × |
| ioDent [®] system | | 1 | Image: A second s |
| Software update via USB | | 1 | 1 |
| Implantmed and Piezomed in one device | | 1 | 1 |
| Handpiece with (LED socket) and cable, thermodisinfectable and sterilisable | Image: A second s | 1 | × |
| Pacemaker reports | Image: A second s | 1 | 1 |
| Boost function | Image: A second s | 1 | × |
| LED light | 1 | 1 | |
| 24 watts | | 1 | |
| 20 watts | ✓* | | |
| 18 watts | | | Image: A second s |

* 24 W with boost function

Plus and Classic module

With the two available module versions **Piezomed Plus** and **Piezomed Classic**, W&H covers every piezosurgical practice need. No matter whether in everyday or intensive use.

Surgery workflow redefined

⊷;

ISQ

Osseointegration

Threading

Stress-free healing. It prevents compression of the bone.

The W&H Osstell ISQ module and the Osstell Beacon enables the healing process of the implant to be monitored, even for high-risk patients.





High-frequency micro vibrations allow cutting with incredible precision.

Implant insertion Controlled insertion of all implant types with a torque of up to 80 NCM.

Documentation

Inform referrers about the implant stability or present your results to a specialist audience.

Technical data

CE 0297

| Туре: | Piezomed SA-320 | Piezomed Plus module SA-435 M | Piezomed Classic module SA-430 M | |
|--|---------------------------|----------------------------------|-------------------------------------|--|
| Supply voltage: | 100-130 V/220-240 V | 100–240 V | | |
| Frequency: | 50–60 Hz | | | |
| Permitted voltage fluctuation: | | ±10% | | |
| Nominal current: | 0.1–1.0 A/0.1–0.5 A | 1.6 A | | |
| Mains frequency: | | 50–60 Hz | | |
| Maximum output US: | 20 W* | 24 W | 18 W | |
| Operating frequency: | | 22–35 kHz | | |
| Coolant flow rate at 100%: | at least 60 ml/min | at least 90 ml/min | | |
| Length of handpiece cable: | 1.8 m/3.5 m | 1.8 m/3.5 m | 1.8 m without light | |
| Dimensions in mm (height × width × depth): | 256 × 305 × 109 | 90 × 140 × 285 | | |
| Weight: | 7 kg | 0.7 kg | 0.6 kg | |
| Foot control: | S-N1/S-NW with SPI dongle | S-N2/S-NW | | |

* 24 W with boost function

Made in Austria

 W&H Dentalwerk Bürmoos GmbH

 Ignaz-Glaser-Straße 53, Postfach 1

 5111 Bürmoos, Austria

 t +43 6274 6236-0

 f +43 6274 6236-55

 office@wh.com

 wh.com